



# PROBLADE ™ 104R Patterned

Pro-Blade™ Patterned Cloth Tape

### **DESCRIPTION**

Specially designed for today's composite hockey sticks, Pro-Blade™ Patterned Cloth Tape from Renfrew Pro™ incorporates an advanced adhesive formulation applied to a polyester/cotton cloth base, resulting in a more substantial cloth tape with increased wear characteristics. This premium cloth tape comes in 7 different patterns – pick your favourite to help identify your stick.

### **APPLICATIONS**

Stick handles and blades

## **PRODUCT BENEFITS**

- Improves grip on handle
- Moisture resistant
- Helps with puck control
- Protects stick from abrasion

## **TECHNICAL PROPERTIES**

Technical Property	Nominal Value	Unit	Test Method
Total Thickness	10.0 (.254)	Mils (mm)	REN TM 20
Adhesion to Steel	28 (7.7)	Oz/Inch (N/25mm)	PSTC - 101 Mod
Adhesion to Backing	20 (5.5)	Oz/Inch (N/25mm)	PSTC - 101 Mod
Tensile Strength	35 (155.7)	lbs. / inch (N/25mm)	

Version: 40 Generated Date: 31 October 2025 Page: 1 of 2

www.renfrewprotape.com Product Code: 104R Patterned

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group ple and its subsidiaries.

### STANDARD PRESENTATIONS

• Patterns: Canadian Flag, Camouflage, Skull & Crossbones, Flames, Team Canada, Rainbow

### **RECOMMENDATIONS**

Application to Surface: Unwind adhesive film or tape and apply the adhesive side to the mounting surface. Apply firm pressure. Recommended application temperature to achieve best results is 65°F (18°C) or above. Proper bonding may not occur unless adhesive and surface material are both at 65°F (18°C) or above.

#### NOTE:

- 1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminates such as powder, dust, or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.
- 2. Shelf life is one year from date of shipment when stored in a cool dry place below 76°F (24°C). Rolls should be stored on end.

Version: 40 Generated Date: 31 October 2025 Page: 2 of 2

www.renfrewprotape.com Product Code: 104R Patterned