



# Scapa 106R

# Foam Under Wrap

# **DESCRIPTION**

Foam Under Wrap is designed as a pre-wrap to be used under our Pro-Grade Athletic Tape to help protect the skin and act as a moisture-absorbing barrier. Renfrew Pro's Foam Under Wrap has many uses in hockey and other sports anytime you need to absorb moisture or create a cushioning hold. Available in 9 colours to match your team uniform.

## **APPLICATIONS**

Wrists/Ankles

# **PRODUCT BENEFITS**

- Absorbs moisture
- Comes in a variety of colours to match team uniforms
- Can be used as a headband
- Can be used to help hold ice packs
- Helps to create a cushioning barrier under trainer's tape

### **TECHNICAL PROPERTIES**

Technical Property	Nominal Value	Unit	Test Method
Cell Count (visual)	55-65	/ In	-
Density	1.60	+/- 10% lbs./cu. Ft	-
Elongation	420	%	-
Physical Properties:	Average	-	-
Tear Resistance	4.2	PPI	-
Tensile Strength	24	PSI	-

Version: 20 Generated Date: 04 November 2025

www.renfrewprotape.com Product Code: 106R

Page: 1 of 2

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

### STANDARD PRESENTATIONS

• Colours: Tan, Purple, Pink, Black, Green, Orange, Red, Yellow, Blue,

### **RECOMMENDATIONS**

Application to Surface: Unwind adhesive film or tape and apply the adhesive side to the mounting surface. Apply firm pressure. Recommended application temperature to achieve best results is 65°F (18°C) or above. Proper bonding may not occur unless adhesive and surface material are both at 65°F (18°C) or above.

NOTE: 1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminates such as powder, dust, or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.

2. Shelf life is one year from date of shipment when stored in a cool dry place below 76°F (24°C). Rolls should be stored on end.

Version: 20 Generated Date: 04 November 2025 Page: 2 of 2

www.renfrewprotape.com Product Code: 106R