



# PROBLADE ™ 503XT

Pro-Blade™ XT Black Cloth Tape

# **DESCRIPTION**

Specially designed for today's composite hockey sticks, Pro-Blade XT™ Black Cloth Tape from Renfrew Pro™ incorporates an advanced adhesive formulation applied to a polyester/cotton cloth base, resulting in a more substantial cloth tape with increased wear characteristics. Pro-Blade™ XT features extra adhesive to last even longer on your stick and provide better grip.

Also available in our Renfrew Pro™ Season Tape Pack with 20 rolls of black Pro-Blade™ Cloth Tape, or our combo pack that includes 6 white and 4 black Pro-Blade™ Cloth Tapes and 10 Polyflex®. Clear Shin Pad Tape rolls.

#### **APPLICATIONS**

· Stick handles and blades

# **PRODUCT BENEFITS**

- Protects stick from abrasion
- Helps with puck control
- Moisture resistant
- Improves grip on handle

Version: 41 Generated Date: 08 December 2025 Page: 1 of 2

www.renfrewprotape.com Product Code: 503XT

### **TECHNICAL PROPERTIES**

| Technical Property  | Nominal Value | Unit                    | Test Method    |
|---------------------|---------------|-------------------------|----------------|
| Total Thickness     | 10.5 (.254)   | Mils (mm)               | REN TM 20      |
| Adhesion to Steel   | 35 (9.6)      | Oz/Inch<br>(N/25mm)     | PSTC - 101 Mod |
| Adhesion to Backing | 23 (6.3)      | Oz/Inch<br>(N/25mm)     | PSTC - 101 Mod |
| Tensile Strength    | 45 (200.2)    | lbs. / inch<br>(N/25mm) | ASTM D 1000    |

### STANDARD PRESENTATIONS

• Colours: Black

### **RECOMMENDATIONS**

## Application to Surface:

Unwind adhesive film or tape and apply the adhesive side to the mounting surface. Apply firm pressure. Recommended application temperature to achieve best results is 65F (18°C) or above. Proper bonding may not occur unless adhesive and surface materials are both at 65°F (18°C) or above.

#### NOTE:

- 1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminates such as powder, dust, or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.
- 2. Shelf life is one year from date of shipment when stored in a cool dry place below 76°F (24°C). Rolls should be stored on end.

Version: 41 Generated Date: 08 December 2025 Page: 2 of 2

www.renfrewprotape.com Product Code: 503XT