



RENFREW ™ M002-SPB

Traction Mat Base

DESCRIPTION

Renfrew Pro Mat Bases are made of durable PVC, and have a foam rubber non-skid backing to keep the base from slipping and prevent damage to the floor. Our base has a convenient carrying handle for portability, and when paired with an M002-SP traction mat, provide a convenient solution for your athletic traction needs. Available in white with black backing.

APPLICATIONS

- Remove dirt and debris for improved traction and increased safety before stepping on the court
- Use for basketball, volleyball, wrestling, badminton, and other indoor sports

PRODUCT BENEFITS

- Improves traction on smooth floors including hardwood and other waxed surfaces
- Increases safety
- Improves performance

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Colour	White	-	-
Backing Colour	Black	-	-
Thickness	3/16 (4.75)	Inch (mm)	-
Composition	PVC	-	-

Version: 6 Generated Date: 25 April 2024 Page: 1 of 2

www.renfrewprotape.com Product Code: M002-SPB

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

STANDARD PRESENTATIONS

Dimension: 18 x 19 (inches)Dimension: 28 x 29 (inches)

Note:

Available with custom logos

RECOMMENDATIONS

Recommended application temperature to achieve best results is 65°F (18°C) or above. Proper bonding may not occur unless adhesive and surface material are both at 65°F (18°C) or above.

NOTE:

- 1) When applying pressure sensitive adhesive films to any surface, be sure that the surface is dry, free from oil or other surface contaminates such as dirt, dust, or release agents.
- 2) Shelf life is one year from date of shipment when stored in a cool dry place below 76°F (24°C)
- 3) The adhesive layer of the mat becomes slippery when wet.

Version: 6 Generated Date: 25 April 2024 Page: 2 of 2

www.renfrewprotape.com Product Code: M002-SPB