

## PROBLADE™ 104R NHL Logos

### Pro-Blade™ NHL Team Patterned Cloth Tape

#### DESCRIPTION

Specially designed for today's composite hockey sticks, Pro-Blade™ NHL Team Patterned Cloth Tape from Renfrew Pro™ incorporates an advanced adhesive formulation applied to a polyester/cotton cloth base, resulting in a more substantial cloth tape with increased wear characteristics. This premium cloth tape comes in a number of different NHL Team patterns – so you can rep your favourite team on the ice.

#### APPLICATIONS

- Stick handles and blades

#### PRODUCT BENEFITS

- Protects stick from abrasion
- Helps with puck control
- Moisture resistant
- Improves grip on handle
- Variety of logos, tape your stick with your favourite team

#### TECHNICAL PROPERTIES

| Technical Property  | Nominal Value | Unit                    | Test Method    |
|---------------------|---------------|-------------------------|----------------|
| Total Thickness     | 10.0 (.254)   | Mils (mm)               | REN TM 20      |
| Adhesion to Steel   | 28 (7.7)      | Oz/Inch<br>(N/25mm)     | PSTC - 101 Mod |
| Adhesion to Backing | 20 (5.5)      | Oz/Inch<br>(N/25mm)     | PSTC - 101 Mod |
| Tensile Strength    | 35(155.72)    | lbs. / inch<br>(N/25mm) | ASTM D 1000    |

## STANDARD PRESENTATIONS

- Patterns: Boston Bruins, Buffalo Sabres, Calgary Flames, Carolina Hurricanes, Chicago Blackhawks, Dallas Stars, Detroit Red Wings, Edmonton Oilers, Florida Panthers, Los Angeles Kings, Montreal Canadiens, New York Rangers, Pittsburgh Penguins, Toronto Maple Leafs

## RECOMMENDATIONS

### Application to Surface:

Unwind adhesive film or tape and apply the adhesive side to the mounting surface. Apply firm pressure. Recommended application temperature to achieve best results is 65°F (18°C) or above. Proper bonding may not occur unless adhesive and surface material are both at 65°F (18°C) or above.

### NOTE:

1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminants such as powder, dust, or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.
2. Shelf life is one year from date of shipment when stored in a cool dry place below 76°F (24°C). Rolls should be stored on end.